

How to install sngrep on your VoipNow server

sngrep is a tool for displaying SIP calls message flows from the terminal of your server. It can be used to display real-time SIP traffic and to process PCAP files (packet captures). Think of it as a specialized tcpdump tool designed for VoIP. It's open-source and it's available [here](#).

This knowledge base article assumes advanced knowledge of the Linux command line and familiarity with the SIP protocol.

Step-by-step guide

Here are the steps to take if you want to install sngrep on your VoipNow server.

Please note that all commands listed in a code block need to be executed as root.

1. If VoipNow is not installed, perform the installation using the command line installer as instructed [here](#).
2. Install the required software packages so that you can download and compile sngrep by running:

```
# yum -y install git libpcap openssl-devel gnutls pcre-devel libpcap-devel ncurses-devel autoconf  
automake gcc make
```

3. Download the sngrep files.

```
# cd ~  
# git clone https://github.com/irontec/sngrep.git  
Cloning into 'sngrep'...  
remote: Counting objects: 4878, done.  
remote: Total 4878 (delta 0), reused 0 (delta 0), pack-reused 4878  
Receiving objects: 100% (4878/4878), 4.06 MiB | 1.98 MiB/s, done.  
Resolving deltas: 100% (3864/3864), done.  
Checking connectivity... done.
```

4. A new folder named sngrep containing the source code will be created. Go to that folder.

```
# cd sngrep
```

5. Run the bootstrap.sh script.

```
# ./bootstrap.sh  
Generating the configure script ...
```

6. Run the configure script.

```
./configure  
checking for a BSD-compatible install... /usr/bin/install -c  
checking whether build environment is sane... yes  
checking for a thread-safe mkdir -p... /usr/bin/mkdir -p  
checking for gawk... gawk  
checking whether make sets $(MAKE)... yes  
checking whether make supports nested variables... yes  
checking whether make supports nested variables... (cached) yes  
checking for style of include used by make... GNU  
checking for gcc... gcc  
checking whether the C compiler works... yes  
checking for C compiler default output file name... a.out  
checking for suffix of executables...  
checking whether we are cross compiling... no  
checking for suffix of object files... o  
checking whether we are using the GNU C compiler... yes  
checking whether gcc accepts -g... yes  
checking for gcc option to accept ISO C89... none needed  
checking dependency style of gcc... gcc3  
checking how to run the C preprocessor... gcc -E  
checking for grep that handles long lines and -e... /usr/bin/grep  
checking for egrep... /usr/bin/grep -E  
checking for ANSI C header files... yes
```

```
checking for sys/types.h... yes
checking for sys/stat.h... yes
checking for stdlib.h... yes
checking for string.h... yes
checking for memory.h... yes
checking for strings.h... yes
checking for inttypes.h... yes
checking for stdint.h... yes
checking for unistd.h... yes
checking minix/config.h usability... no
checking minix/config.h presence... no
checking for minix/config.h... no
checking whether it is safe to define __EXTENSIONS__... yes
checking for gcc... (cached) gcc
checking whether we are using the GNU C compiler... (cached) yes
checking whether gcc accepts -g... (cached) yes
checking for gcc option to accept ISO C89... (cached) none needed
checking dependency style of gcc... (cached) gcc3
checking for g++... no
checking for c++... no
checking for gpp... no
checking for aCC... no
checking for CC... no
checking for cxx... no
checking for cc++... no
checking for cl.exe... no
checking for FCC... no
checking for KCC... no
checking for RCC... no
checking for xlc_r... no
checking for xlc... no
checking whether we are using the GNU C++ compiler... no
checking whether g++ accepts -g... no
checking dependency style of g++... none
checking whether ln -s works... yes
checking for egrep... (cached) /usr/bin/grep -E
checking for pthread_create in -lpthread... yes
checking for pcap_open_offline in -lpcap... yes
checking pcap.h usability... yes
checking pcap.h presence... yes
checking for pcap.h... yes
checking ncurses.h usability... yes
checking ncurses.h presence... yes
checking for ncurses.h... yes
checking for initscr in -lncurses... yes
checking for new_panel in -lpanel... yes
checking for new_form in -lform... yes
checking for new_item in -lmenu... yes
```

configure:

configure: sngrep configure finished

configure: =====

configure: GnuTLS Support : no

configure: OpenSSL Support : no

configure: Unicode Support : no

configure: Perl Expressions Support : no

configure: IPv6 Support : no

configure: EEP Support : no

configure: =====

configure:

checking that generated files are newer than configure... done

configure: creating ./config.status

config.status: creating Makefile

config.status: creating src/Makefile

config.status: creating config/Makefile

config.status: creating doc/Makefile

```
config.status: creating tests/Makefile
config.status: creating src/config.h
config.status: executing depfiles commands
```

7. Compile sngrep with the make command.

```
# make
Making all in src
make[1]: Entering directory `/root/sngrep/src'
make all-am
make[2]: Entering directory `/root/sngrep/src'
CC      capture.o
CC      address.o
CC      packet.o
CC      sip.o
CC      sip_call.o
CC      sip_msg.o
CC      sip_attr.o
CC      main.o
CC      option.o
CC      group.o
CC      filter.o
CC      keybinding.o
CC      media.o
CC      setting.o
CC      rtp.o
CC      util.o
CC      vector.o
CC      ui_panel.o
CC      scrollbar.o
CC      ui_manager.o
CC      ui_call_list.o
CC      ui_call_flow.o
CC      ui_call_raw.o
CC      ui_stats.o
CC      ui_filter.o
CC      ui_save.o
CC      ui_msg_diff.o
CC      ui_column_select.o
CC      ui_settings.o
CCLD    sngrep
make[2]: Leaving directory `/root/sngrep/src'
make[1]: Leaving directory `/root/sngrep/src'
Making all in config
make[1]: Entering directory `/root/sngrep/config'
make[1]: Nothing to be done for `all'.
make[1]: Leaving directory `/root/sngrep/config'
Making all in doc
make[1]: Entering directory `/root/sngrep/doc'
make[1]: Nothing to be done for `all'.
make[1]: Leaving directory `/root/sngrep/doc'
Making all in tests
make[1]: Entering directory `/root/sngrep/tests'
make[1]: Nothing to be done for `all'.
make[1]: Leaving directory `/root/sngrep/tests'
make[1]: Entering directory `/root/sngrep'
make[1]: Nothing to be done for `all-am'.
make[1]: Leaving directory `/root/sngrep'
```

8. Install sngrep with the make install command.

```

# make install
Making install in src
make[1]: Entering directory `/root/sngrep/src'
make[2]: Entering directory `/root/sngrep/src'
  /usr/bin/mkdir -p '/usr/local/bin'
  /usr/bin/install -c sngrep '/usr/local/bin'
make[2]: Nothing to be done for `install-data-am'.
make[2]: Leaving directory `/root/sngrep/src'
make[1]: Leaving directory `/root/sngrep/src'
Making install in config
make[1]: Entering directory `/root/sngrep/config'
make[2]: Entering directory `/root/sngrep/config'
  /usr/bin/mkdir -p '/usr/local/etc'
  /usr/bin/install -c -m 644 sngrepc '/usr/local/etc'
make[2]: Nothing to be done for `install-data-am'.
make[2]: Leaving directory `/root/sngrep/config'
make[1]: Leaving directory `/root/sngrep/config'
Making install in doc
make[1]: Entering directory `/root/sngrep/doc'
make[2]: Entering directory `/root/sngrep/doc'
make[2]: Nothing to be done for `install-exec-am'.
  /usr/bin/mkdir -p '/usr/local/share/man/man8'
  /usr/bin/install -c -m 644 sngrep.8 '/usr/local/share/man/man8'
make[2]: Leaving directory `/root/sngrep/doc'
make[1]: Leaving directory `/root/sngrep/doc'
Making install in tests
make[1]: Entering directory `/root/sngrep/tests'
make[2]: Entering directory `/root/sngrep/tests'
make[2]: Nothing to be done for `install-exec-am'.
make[2]: Nothing to be done for `install-data-am'.
make[2]: Leaving directory `/root/sngrep/tests'
make[1]: Leaving directory `/root/sngrep/tests'
make[1]: Entering directory `/root/sngrep'
make[2]: Entering directory `/root/sngrep'
make[2]: Nothing to be done for `install-exec-am'.
make[2]: Nothing to be done for `install-data-am'.
make[2]: Leaving directory `/root/sngrep'
make[1]: Leaving directory `/root/sngrep'

```

9. sngrep is now installed into /usr/local/bin/sngrep which should be already in your path. You may launch it with the sngrep command:

```
# sngrep
```

After starting sngrep, you'll be presented with a text-mode, interactive interface which can be navigated with the arrow keys and quit with the Esc key.

How to make the most of SNGREP

Initialize a softphone which registers to your VoipNow server, and the REGISTER and the SUBSCRIBE methods sent by the phone will appear in the console right away. You can clear the list of captured messages by pressing the F5 key, as indicated in the legend at the bottom of the screen.

ID	Method	SIP From	SIP To	Msgs	Source	Destination	Call State
[] 1	REGISTER	0003*002@10.150.8.21:5060	0003*002@10.150.8.21:5060	4	192.168.3.189:56712	10.150.8.21:5060	
[] 2	SUBSCRIBE	0003*002@10.150.8.21:5060	0003*002@10.150.8.21:5060	4	192.168.3.189:56712	10.150.8.21:5060	

You can move the cursor between the displayed packets using the arrow keys. For details about a specific SIP method, press ENTER. You'll get a graphical flow of the packets exchanged between your phone and the VoipNow server. You may navigate through the flow using the same arrow keys - the selected message details will be displayed on the right of the window.

```

Call flow for NthlMTA0YjY2ZQwOThhNTg2MWEyNTVxMjEzY2ZWE. (Color by Request/Response)
192.168.3.189:56712 10.150.8.21:5060 REGISTER sip:10.150.8.21:5060 SIP/2.0
Via: SIP/2.0/UDP 192.168.3.189:56712;branch=z9hG4bK-d8754z-b42c2d6ac977f91c-1---d8754z-;rport
Max-Forwards: 70
Contact: <sip:0003*002@192.168.3.189:56712;rinstance=1c1bf515683da4b4>
To: "4PSATEST"<sip:0003*002@10.150.8.21:5060>
From: "4PSATEST"<sip:0003*002@10.150.8.21:5060>;tag=0a390a23
Call-ID: NthlMTA0YjY2ZQwOThhNTg2MWEyNTVxMjEzY2ZWE.
CSeq: 1 REGISTER
Expires: 120
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REGISTER, SUBSCRIBE, NOTIFY, REFER, INFO, MESSAGE
Supported: replaces
User-Agent: 3CXPhone 6.0.26523.0
Content-Length: 0
X-Dc: PHNpcDowMDazKjAwMkAOTIuMTY4LjMuMTg5OjU2NzEyO3JpbnN0YW5jZT0xYzF1ZjUxNTY4M2RhNGI0Pg==
X-Dv: U0lQZlUuMC9VRfAgMTkYlE2OC4zLjE4OT0lNjcxMjIcmFuY2g9ejl0RzRlSylkODc1NH0tYjYyZjYkNmFjOTc3ZjkyY0xLS0tZDg3NTR6LTtvcG9ydA==

12:34:16.463983 REGISTER
+0.001068 401 Unauthorized
12:34:16.465051 REGISTER
+0.102470 401 Unauthorized
12:34:16.567521 REGISTER
+0.005218 200 OK
12:34:16.572739 REGISTER
+0.141789 401 Unauthorized
12:36:04.714528 REGISTER
+0.001707 401 Unauthorized
12:36:04.716235 REGISTER
+0.102891 401 Unauthorized
12:36:04.819626 REGISTER
+0.006869 200 OK
12:36:04.826486 REGISTER

```

Pressing ENTER again will show the packet in raw mode.

```

2016/05/13 12:34:16.463983 192.168.3.189:56712 -> 10.150.8.21:5060
REGISTER sip:10.150.8.21:5060 SIP/2.0
Via: SIP/2.0/UDP 192.168.3.189:56712;branch=z9hG4bK-d8754z-b42c2d6ac977f91c-1---d8754z-;rport
Max-Forwards: 70
Contact: <sip:0003*002@192.168.3.189:56712;rinstance=1c1bf515683da4b4>
To: "4PSATEST"<sip:0003*002@10.150.8.21:5060>
From: "4PSATEST"<sip:0003*002@10.150.8.21:5060>;tag=0a390a23
Call-ID: NthlMTA0YjY2ZQwOThhNTg2MWEyNTVxMjEzY2ZWE.
CSeq: 1 REGISTER
Expires: 120
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REGISTER, SUBSCRIBE, NOTIFY, REFER, INFO, MESSAGE
Supported: replaces
User-Agent: 3CXPhone 6.0.26523.0
Content-Length: 0
X-Dc: PHNpcDowMDazKjAwMkAOTIuMTY4LjMuMTg5OjU2NzEyO3JpbnN0YW5jZT0xYzF1ZjUxNTY4M2RhNGI0Pg==
X-Dv: U0lQZlUuMC9VRfAgMTkYlE2OC4zLjE4OT0lNjcxMjIcmFuY2g9ejl0RzRlSylkODc1NH0tYjYyZjYkNmFjOTc3ZjkyY0xLS0tZDg3NTR6LTtvcG9ydA==

```

Here are the 4 stages of a SIP registration:

1. The initial REGISTER sent by the phone (informing the server of his presence).

```

Call flow for NthlMTA0YjY2ZQwOThhNTg2MWEyNTVxMjEzY2ZWE. (Color by Request/Response)
192.168.3.189:56712 10.150.8.21:5060 REGISTER sip:10.150.8.21:5060 SIP/2.0
Via: SIP/2.0/UDP 192.168.3.189:56712;branch=z9hG4bK-d8754z-7233e2a6b5472d-1---d8754z-;rport
Max-Forwards: 70
Contact: <sip:0003*002@192.168.3.189:56712;rinstance=1c1bf515683da4b4>
To: "4PSATEST"<sip:0003*002@10.150.8.21:5060>
From: "4PSATEST"<sip:0003*002@10.150.8.21:5060>;tag=0a390a23
Call-ID: NthlMTA0YjY2ZQwOThhNTg2MWEyNTVxMjEzY2ZWE.
CSeq: 2 REGISTER
Expires: 120
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REGISTER, SUBSCRIBE, NOTIFY, REFER, INFO, MESSAGE
Supported: replaces
User-Agent: 3CXPhone 6.0.26523.0
Authorization: Digest username="0003*002", realm="10.150.8.21", nonce="VxX51c1cydvp1p9/ha3U5q6WWRqD", uri="sip:10.150.8.21:5060"
WWW-Authenticate: Digest realm="10.150.8.21", nonce="VxX51c1cydvp1p9/ha3U5q6WWRqD", uri="sip:10.150.8.21:5060"
X-Dc: PHNpcDowMDazKjAwMkAOTIuMTY4LjMuMTg5OjU2NzEyO3JpbnN0YW5jZT0xYzF1ZjUxNTY4M2RhNGI0Pg==
X-Dv: U0lQZlUuMC9VRfAgMTkYlE2OC4zLjE4OT0lNjcxMjIcmFuY2g9ejl0RzRlSylkODc1NH0tYjYyZjYkNmFjOTc3ZjkyY0xLS0tZDg3NTR6LTtvcG9ydA==

12:34:16.463983 REGISTER
+0.001068 401 Unauthorized
12:34:16.465051 REGISTER
+0.102470 401 Unauthorized
12:34:16.567521 REGISTER
+0.005218 200 OK
12:34:16.572739 REGISTER
+0.141789 401 Unauthorized
12:36:04.714528 REGISTER
+0.001707 401 Unauthorized
12:36:04.716235 REGISTER
+0.102891 401 Unauthorized
12:36:04.819626 REGISTER
+0.006869 200 OK
12:36:04.826486 REGISTER
12:37:52.994899 REGISTER
+0.002763 401 Unauthorized
12:37:52.997662 REGISTER
+0.154674 200 OK
12:37:53.102336 REGISTER
+0.008714 200 OK
12:37:53.109050 REGISTER
+0.003145 200 OK

```

2. The 401 Unauthorized sent by the server to the phone (containing the challenge to which the phone has to reply).

```

Call flow for NthlMTA0YjY2ZQwOThhNTg2MWEyNTVxMjEzY2ZWE. (Color by Request/Response)
192.168.3.189:56712 10.150.8.21:5060 SIP/2.0 200 OK
Via: SIP/2.0/UDP 192.168.3.189:56712;branch=z9hG4bK-d8754z-7233e2a6b5472d-1---d8754z-;rport=56712
Max-Forwards: 70
From: "4PSATEST"<sip:0003*002@10.150.8.21:5060>;tag=0a390a23
Call-ID: NthlMTA0YjY2ZQwOThhNTg2MWEyNTVxMjEzY2ZWE.
CSeq: 2 REGISTER
Server: VoIPnow PBX
Content-Length: 0

12:34:16.463983 REGISTER
+0.001068 401 Unauthorized
12:34:16.465051 REGISTER
+0.102470 401 Unauthorized
12:34:16.567521 REGISTER
+0.005218 200 OK
12:34:16.572739 REGISTER
+0.141789 401 Unauthorized
12:36:04.714528 REGISTER
+0.001707 401 Unauthorized
12:36:04.716235 REGISTER
+0.102891 401 Unauthorized
12:36:04.819626 REGISTER
+0.006869 200 OK
12:36:04.826486 REGISTER
12:37:52.994899 REGISTER
+0.002763 401 Unauthorized
12:37:52.997662 REGISTER
+0.154674 200 OK
12:37:53.102336 REGISTER
+0.008714 200 OK
12:37:53.109050 REGISTER
+0.003145 200 OK

```

3. The second REGISTER message sent by the phone (with the valid credentials, user ID and password).

```

Call flow for NthlMTA0YjY2ZQwOThhNTg2MWEyNTVxMjEzY2ZWE. (Color by Request/Response)
192.168.3.189:56712 10.150.8.21:5060 REGISTER sip:10.150.8.21:5060 SIP/2.0
Via: SIP/2.0/UDP 192.168.3.189:56712;branch=z9hG4bK-d8754z-b42c2d6ac977f91c-1---d8754z-;rport
Max-Forwards: 70
Contact: <sip:0003*002@192.168.3.189:56712;rinstance=1c1bf515683da4b4>
To: "4PSATEST"<sip:0003*002@10.150.8.21:5060>
From: "4PSATEST"<sip:0003*002@10.150.8.21:5060>;tag=0a390a23
Call-ID: NthlMTA0YjY2ZQwOThhNTg2MWEyNTVxMjEzY2ZWE.
CSeq: 3 REGISTER
Expires: 120
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REGISTER, SUBSCRIBE, NOTIFY, REFER, INFO, MESSAGE
Supported: replaces
User-Agent: 3CXPhone 6.0.26523.0
Content-Length: 0
X-Dc: PHNpcDowMDazKjAwMkAOTIuMTY4LjMuMTg5OjU2NzEyO3JpbnN0YW5jZT0xYzF1ZjUxNTY4M2RhNGI0Pg==
X-Dv: U0lQZlUuMC9VRfAgMTkYlE2OC4zLjE4OT0lNjcxMjIcmFuY2g9ejl0RzRlSylkODc1NH0tYjYyZjYkNmFjOTc3ZjkyY0xLS0tZDg3NTR6LTtvcG9ydA==

12:34:16.463983 REGISTER
+0.001068 401 Unauthorized
12:34:16.465051 REGISTER
+0.102470 401 Unauthorized
12:34:16.567521 REGISTER
+0.005218 200 OK
12:34:16.572739 REGISTER
+0.141789 401 Unauthorized
12:36:04.714528 REGISTER
+0.001707 401 Unauthorized
12:36:04.716235 REGISTER
+0.102891 401 Unauthorized
12:36:04.819626 REGISTER
+0.006869 200 OK
12:36:04.826486 REGISTER
12:37:52.994899 REGISTER
+0.002763 401 Unauthorized
12:37:52.997662 REGISTER
+0.154674 200 OK
12:37:53.102336 REGISTER
+0.008714 200 OK
12:37:53.109050 REGISTER
+0.003145 200 OK

```

4. The 200 OK confirming the phone has registered correctly with the server.

```
Call flow for 192.168.3.189:56712 to 10.150.8.21:5060 (Color by Request/Response)
-----
12:34:16.463989 | 192.168.3.189:56712 | REGISTER | 401 Unauthorized |
+0.000000 |
12:34:16.465051 | 10.150.8.21:5060 | REGISTER | 200 OK |
+0.000000 |
12:34:16.567921 | 192.168.3.189:56712 | REGISTER | 401 Unauthorized |
+0.000000 |
12:34:16.572739 | 10.150.8.21:5060 | REGISTER | 200 OK |
+0.000000 |
12:36:04.714528 | 192.168.3.189:56712 | REGISTER | 401 Unauthorized |
+0.000000 |
12:36:04.716235 | 10.150.8.21:5060 | REGISTER | 200 OK |
+0.000000 |
12:36:04.819626 | 192.168.3.189:56712 | REGISTER | 401 Unauthorized |
+0.000000 |
12:36:04.826486 | 10.150.8.21:5060 | REGISTER | 200 OK |
+0.000000 |
12:37:52.994899 | 192.168.3.189:56712 | REGISTER | 401 Unauthorized |
+0.000000 |
12:37:52.997662 | 10.150.8.21:5060 | REGISTER | 200 OK |
+0.000000 |
12:37:53.102336 | 192.168.3.189:56712 | REGISTER | 401 Unauthorized |
+0.000000 |
12:37:53.109050 | 10.150.8.21:5060 | REGISTER | 200 OK |
+0.000000 |
```

Place a call to *52 (the echo test) and you'll see the call appear in the list.

Pressing ENTER will open a call flow diagram illustrating the communication between the phone and the SIP/PBX components of VoipNow.

sngrep - SIP messages flow viewer								
Current Mode: Online		Dialogs: 1						
Display Filter:								
	Method	SIP From	SIP To	Mags	Source	Destination	Call State	
[]	1	INVITE	0003*002@10.150.8.21:5060	*52@10.150.8.21:5060	16	192.168.3.189:56712	10.150.8.21:5060	IN CALL

```
Call flow for 192.168.3.189:56712 to 10.150.8.21:5060 (Color by Request/Response)
-----
12:44:24.810447 | 192.168.3.189:56712 | INVITE (SDP) |
+0.000000 |
12:44:24.819488 | 10.150.8.21:5060 | 100 trying -- your call is |
+0.000244 |
12:44:24.819732 | 192.168.3.189:56712 | INVITE (SDP) |
+0.000000 |
12:44:24.827323 | 10.150.8.21:5060 | 100 Trying |
+0.019665 |
12:44:24.846988 | 192.168.3.189:56712 | 200 OK (SDP) |
+0.000000 |
12:44:24.849422 | 10.150.8.21:5060 | ACK |
+0.102886 |
12:44:24.952308 | 192.168.3.189:56712 | ACK |
+0.000000 |
12:44:24.955486 | 10.150.8.21:5060 | ACK |
+0.996801 |
12:44:25.952287 | 192.168.3.189:56712 | INFO |
+0.000000 |
12:44:25.958776 | 10.150.8.21:5060 | INFO |
+0.104632 |
12:44:26.063408 | 192.168.3.189:56712 | 415 Unsupported Media Type |
+0.000000 |
12:44:26.063787 | 10.150.8.21:5060 | 415 Unsupported Media Type |
+11.884265 |
12:44:37.948052 | 192.168.3.189:56712 | INFO |
+0.000000 |
12:44:37.950395 | 10.150.8.21:5060 | 415 Unsupported Media Type |
+0.102881 |
12:44:38.053276 | 192.168.3.189:56712 | 415 Unsupported Media Type |
+0.000446 |
12:44:38.053722 | 10.150.8.21:5060 | 415 Unsupported Media Type |
```

More great SNGREP features

For example, you can compare two SIP packets by checking them with the Space key. Once the second packet is checked, the differences between the two packets will be automatically shown in a separate window.

```
sngrep - SIP messages flow viewer
-----
2016/05/13 12:15:01:30:774098 192.168.3.189:56712 -> 10.150.8.21:5060
REGISTER sip:10.150.8.21:5060 SIP/2.0
Via: SIP/2.0/UDP 192.168.3.189:56712;branch=zshG4bK-d8754z-2e229331131648745-1---d8754z--rport
Max-Forwards: 70
Contact: <sip:0003*002@10.150.8.21:5060>;rinstance=ic1bf515683da4b4
To: *4PSATEST*<sip:0003*002@10.150.8.21:5060>
From: *4PSATEST*<sip:0003*002@10.150.8.21:5060>;tag=0a390a23
Call-ID: NThLMTA0YjY2ZWQ2OThhMmYyNTVhMjEzY2ZmMTYwZDQzNTRELTtY0zDg5dA=
CSeq: 19 REGISTER
Expires: 120
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REGISTER, SUBSCRIBE, NOTIFY, REFER, INFO, MESSAGE
Supported: replaces
User-Agent: 3CXPhone 6.0.26523.0
Authorization: Digest username="0003*002", realm="10.150.8.21", nonce="VxXNFc1zSg6UjWf5N307pF2eZ0S", uri="sip:10.150.8.21:5060", response="d972b301d7e462f44f6c6bb357bc", algorithm=MD5
Content-Length: 0
X-Do: PHNpcDowMDAaKjAwMkxOTU1MTY4LjMuMTp5OjU2NzEzY2ZmMTYwZDQzNTRELTtY0zDg5dA=
X-Dv: U0lqZzUwMzYyZWQ2OThhMmYyNTVhMjEzY2ZmMTYwZDQzNTRELTtY0zDg5dA=
X-Dmp: NDAMMDY=
-----
2016/05/13 12:15:01:30:877033 192.168.3.189:56712 -> 10.150.8.21:5060
REGISTER sip:10.150.8.21:5060 SIP/2.0
Via: SIP/2.0/UDP 192.168.3.189:56712;branch=zshG4bK-d8754z-493e3156972b151---d8754z--rport
Max-Forwards: 70
Contact: <sip:0003*002@10.150.8.21:5060>;rinstance=ic1bf515683da4b4
To: *4PSATEST*<sip:0003*002@10.150.8.21:5060>
From: *4PSATEST*<sip:0003*002@10.150.8.21:5060>;tag=0a390a23
Call-ID: NThLMTA0YjY2ZWQ2OThhMmYyNTVhMjEzY2ZmMTYwZDQzNTRELTtY0zDg5dA=
CSeq: 20 REGISTER
Expires: 120
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REGISTER, SUBSCRIBE, NOTIFY, REFER, INFO, MESSAGE
Supported: replaces
User-Agent: 3CXPhone 6.0.26523.0
Authorization: Digest username="0003*002", realm="10.150.8.21", nonce="VxXNFc1zSg6UjWf5N307pF2eZ0S", uri="sip:10.150.8.21:5060", response="d972b301d7e462f44f6c6bb357bc", algorithm=MD5
Content-Length: 0
X-Do: PHNpcDowMDAaKjAwMkxOTU1MTY4LjMuMTp5OjU2NzEzY2ZmMTYwZDQzNTRELTtY0zDg5dA=
X-Dv: U0lqZzUwMzYyZWQ2OThhMmYyNTVhMjEzY2ZmMTYwZDQzNTRELTtY0zDg5dA=
X-Dmp: NDAMMDY=
```

If you press F2 and F3 in a call flow, you will be able to see SDP and RTP information.

```

Call Flow for 192.168.3.189:56712 10.150.8.21:5060 10.150.8.21:5050 (Color by Request/Response)
[Invite] sip:4841@10.150.8.21:5060 SIP/2.0
Via: SIP/2.0/UDP 192.168.3.189:56712;branch=19044bR-d8754+-5a098a520b7fb030-1---d8754z-rport
Max-Forwards: 70
Contact: <sip:0003@0028102.168.3.189:56712;instance=1c1bf515683de4b>
To: <sip:52810.150.8.21:5060>
From: *SPSATEST*csip:0003@002810.150.8.21:5060;tag=6484871b
Call-Info: <url:voicertp://10.150.8.21:5050>
CSeq: 1 INVITE
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REGISTER, SUBSCRIBE, NOTIFY, REFER, INFO, MESSAGE
Content-Type: application/sdp
Supported: replace
Content-Length: 404
X-Dr: PHpPDownMazKAmMKAaCIuHT4i;MuHTG0U2HsY03JpbzNYR8;IT0kTf1jDkHTY4M2HhH10Fv==
X-Dr: HDqgIaMwYRfAmMKAaCIuHT4i;K4KorRlycmJycimaz2qhe;1k8z15yAk0c1H8ocwMwvrbhATV;dy;AmMCAzL5cZDgZNT8LITy089yda==
X-Disp: MRYL;E2004i;340==
X-Disp: HDAdMI=
v=0
o=3mVCE 168582220 101622390 IN IP4 192.168.3.189
s=3mVCE Audio Call
c=IN IP4 192.168.3.189
t=0
m=audio 40012 RTP/AVP 0 8 3 98
a=rtpmap:0 PCMU/8000
a=rtpmap:8 PCMA/8000
a=rtpmap:3 GSM/8000
a=rtpmap:98 telephone-event/8000
a=rtcp:18 0-15
a=ptime:20
a=sendrecv
m=video 40010 RTP/AVP 34
c=IN IP4 192.168.3.189
a=rtpmap:34 H263/90000
a=frap:34 QCIF=1;CIF=1;SQCIF=1;CIF+1
a=sendrecv
12:49:37.124992 | RTP (192.168.3.189) | | |
| audio 40012 (g711a) | | |
| video 40011 (h263) | | |
12:49:37.131203 | 100 trying -- your call is | | |
+0.006211 | | |
12:49:37.131337 | 100 Trying | | |
+0.000334 | | |
12:49:37.131337 | 100 Trying | | |
+0.005904 | | |
12:49:37.131724 | 200 (10.150.8.21) | | |
+0.008488 | | |
+0.518736 | | |
12:49:37.150977 | 200 (10.150.8.21) | | |
| audio 16015 (g711a) | | |
| video 0 (h263) | | |
+0.001199 | | |
12:49:37.152176 | RTP (g711a) 298 | | |
| 40012 -----> 16015 | | |
+0.100005 | | |
12:49:37.254934 | | |
+0.008488 | | |
12:49:37.256540 | RTP (g711a) 249 | | |
| 40012 <----- 16015 | | |
+0.492884 | | |
12:49:38.249424 | INFO | | |
+0.000000 | | |
12:49:38.255246 | 415 Unsupported Media Type | | |
+0.002039 | | |
12:49:38.357425 | | |
+0.001371 | | |
12:49:38.358706 | BYE | | |
+4.455127 | | |
12:49:43.17313 | | |
+0.000000 | | |
12:49:43.174045 | 200 OK | | |
+0.000000 | | |
12:49:43.174624 | | |
+0.000702 | | |
12:49:43.175826 | | |

```

There are more options and features in sngrep, so feel free to explore further. While a bit more cumbersome to use than Wireshark, sngrep can help you quickly debug SIP problems on your server.

Related articles

- [How to install sngrep on your VoipNow server](#)
- [How to do a data migration between two DNSManager servers](#)
- [Primary and secondary server setup for 4PSA DNS Manager](#)
- [How to Allow 4PSA Access to the Server](#)
- [How to interact with RabbitMQ](#)