

List CDR

This method allows getting a list of calls from the call history of a system in particular contexts such as User, Organization or global.

- [Request/Response model](#)
 - [Overview](#)
 - [Request](#)
 - [Response](#)
- [Examples](#)

Request/Response model

Overview

Use this service to retrieve a list of phone calls that occurred in the system.

If successful, the Service returns a collection of [PhoneCall](#) resources and the [PhoneCallStat](#) associated.

The request is made by an App that is registered to a User account.

To list the CDR in a desired context, issue a HTTP GET request:

Model

```
HTTP-Method      = "GET"
URI-Fragment     = "/uapi/cdr/" User-Id
Query-Parameters = Get-CDR-Request-Parameters
Request-Payload  = null

Return-Object    = Collection<PhoneCallRecord>
```

Example

```
GET /uapi/cdr/33 HTTP/1.1
HOST uapi.voipnow.com Authorization: Bearer token Content Type: application/json
```

Request

A request to list the Phone Calls must support the [Standard-Request-Parameters](#):

Restriction to Standard Request Parameters

Name	Type	Description
count	Number	The page size of a collection. Maximum possible value is 5000. Default: 20 entries
filterBy	String	Records can be filtered only by source, destination, published and answered.
filterValue	String	The value to filter by.
startIndex	Number	The start index of the paged collection. Maximum possible value is 5000. Default: 0

Custom Request Parameters

The following parameters can also be used:

Name	Type	Description
source	UAPI-Extension-Number	The number that made the call. Can be an extended extension number or a public phone number.
destination	UAPI-Extension-Number	The number that received the call. Can be an extended extension number or a public phone number.

startDate	Date	Date when the call was answered.
endDate	Date	Date when the call was answered.
saveStartDate	Date	Date when the call was saved to the database.
saveEndDate	Date	Date when the call was saved to the database.
disposition	Number	The call disposition: 0 - ANSWERED - to fetch calls that were answered; 1 - BUSY - to get the calls that were answered with a busy tone 2 - FAILED - to fetch the calls that have failed 3 - NO ANSWER - to fetch the calls that had no answer 4 - UNKNOWN - to fetch the unknown calls 5 - NOT ALLOWED - to fetch the calls that were not allowed.
fields	Array<String>	An array of PhoneCallStat field names. For standard values, please see the PhoneCallStat resource.

Response

Success

If successful, returns a collection of [PhoneCall](#) resources, the [PhoneCallStat](#) associated, and the following HTTP statuses:

HTTP Code	Description
200	The list of phone calls is returned.
204	There are no phone calls to be returned.

Failure

When it fails, the request returns the following error codes:

HTTP Code	Code	Description
400	fields_invalid	Value supplied in fields parameter is missing or invalid. The parameter must be set to a value of consisting of the name of the possible PhoneCall fields separated by a comma (e.g. extension, id, answered).
400	count_invalid	Value supplied in count parameter is missing or invalid. The parameter must be set to a numeric value lower than 5000.
400	filterby_invalid	Value supplied in filterBy parameter is missing or invalid. The parameter must be set to the name of a field used by CRD.
400	filterop_invalid	Value supplied in filterOp parameter is missing or invalid. The parameter must be set to one of the values: contains, equals, startsWith or present.
400	filtervalue_invalid	Value supplied in filterValue parameter is missing or invalid. The parameter must be set to a string value.
400	sortorder_invalid	Value supplied in sortOrder parameter is missing or invalid. The parameter must be set to one of the values: ascending or descending.
400	startindex_invalid	Value supplied in startIndex parameter is missing or invalid. The parameter must be set to a numeric value, higher or equal with 0 and lower than 5000.
400	cdr_user_invalid	Value supplied in the URI-Fragment as userId is invalid. The parameter must reference the Id of an user or can be set to @me or @viewer.
400	cdr_start_date_invalid	Value supplied in startDate parameter is invalid.
400	cdr_end_date_invalid	Value supplied in endDate parameter is invalid.
400	cdr_source_invalid	Value supplied in source parameter is invalid.
400	cdr_destination_invalid	Value supplied in destination parameter is invalid.
400	cdr_flow_invalid	Value supplied in flow parameter is invalid.

400	cdr_disposition_invalid	Value supplied in disposition parameter is invalid.
400	cdr_save_start_date_invalid	Value supplied in saveStartDate parameter is invalid.
400	cdr_save_end_date_invalid	Value supplied in saveEndDate parameter is invalid.

Examples

Below you can find an example that will help you understand the request and the response.

This example lists the phone calls that were assigned to the User with Id 33. The request is made by an App on behalf of the Administrator.

HTTP Request
<pre>GET /uapi/cdr/?ownerId=33 HTTP/1.1 HOST uapi.voipnow.com Authorization: Bearer token Content Type: application/json</pre>

Assuming the request has been successful, the Service returns the following answer:

HTTP Response

HTTP/1.1 200 OK

```
...
{
  "entry":
  {
    "53bec7de3c242d5f87e5":
    {
      "id": "53bec7de3c242d5f87e5",
      "ownerId": "33",
      ...
      "phoneCallView": [
        {
          "source": "14141555",
          "destination": "0003*002",
          ...
        },
        {
          "source": "14141555",
          "destination": "0003*006",
          ...
        }
      ]
    },
    "ad5a65672e3f783665c0":
    {
      "id": "ad5a65672e3f783665c0",
      "ownerId": "33",
      "phoneCallView": [
        {
          "source": "14141555",
          "destination": "0003*002",
          ...
        }
      ]
    },
    ...
  },
  "startIndex": 0,
  "totalResults": 34922,
  "itemsPerPage": 20,
  "filtered": true,
  "sorted": true,
  "phoneCallStat": [
    {
      "type": 0,
      "total": 17558,
      "unanswered": "4063",
      "busy": "5435",
      "failed": "3313",
      "unknown": 0,
      "unallowed": 0,
      "answered": "4747"
    },
    {
      "type": 1,
      ...
    }
  ],
  "paging": {...}
}
```