PhoneCallEvents Resource

This page describes the representation of the resources used by the Extension PhoneCallEvent Service.

PhoneCallEvent resource

A phone call event is represented by the UnifiedAPI as a PhoneCallEvent resource.

JSON representation

The example below contains the PhoneCallEvent in JSON representation. All fields are fictitious.

```
{
  "type": "0",
  "id": "NqeyDRqo4FtabmFj8gNWq3hsiGNYyq",
  "method": "0",
  "note": "My extension event is awesome",
  "url": "http://mynEvent.com/SaveMyPhoneCallDetails",
  "status": "1",
  "modified": "2012-07-10T18:16:12+03:00",
  "links": {"self":"https://x.x.x.x/uapi/extensions/@me/0003*210/phoneCallEvents/0
/NqeyDRqo4FtabmFj8gNWq3hsiGNYyq"}
 }
```

PhoneCallEvent fields

Name	Type	Description
type	Number	Type of the Phone Call Event. **0** for Dial-In **1** for Dial-Out **2** for Hangup **3** for Answer incoming call **4** for Answer outgoing call
id	String	Id of the Phone Call Event. Must be alpha-numeric and 1 to 255 characters long.
url	String	The URL that is accessed when the extension receives, makes or terminates a phone call. Must be encoded using the RFC 3986.
method	Number	The HTTP method used by the server to access the URL when an event occurs. **0** for GET **1** for POST
status	Number	The status of the event. **0** for disabled **1** for enabled
note	String	Notes about the event.
modified	Date	Date when the event was last modified.

Related Topics
Create PhoneCallEvents

Update PhoneCallEvents

List PhoneCallEvents

Delete PhoneCallEvents