

# Create PhoneCallEvents

This method allows adding new phone call events in particular contexts such as User, Organization or global.

- [Request/Response model](#)
  - [Overview](#)
  - [Request](#)
  - [Response](#)
- [Examples](#)

## Request/Response model

### Overview

Use this request to add call events to an Extension.

If successful, the Service returns the Id of the newly created [PhoneCallEvent](#), which is later used to [query the status](#) of the phone call event.

The request is made by an App that is registered to a User account.

To create a PhoneCallEvent, issue a HTTP POST request:

#### Model

```
HTTP-Method      = "POST"
URI-Fragment     = "/uapi/extensions/" User-Id "/" Extension-Number "/phoneCallEvents/"
Query-Parameters = null
Request-Payload  = PhoneCallEvent

Return-Object    = PhoneCallEvent
```

#### Example

```
POST /uapi/extensions/@me/0003*210/phoneCallEvents HTTP/1.1
HOST uapi.voipnow.com
Content Type: application/json
Authorization: Bearer token

{
  "type": "0",
  "method": "0",
  "note": "My phone call event is awesome",
  "url": "http://myevent.com/SaveMyPhoneCallDetails",
  "status": "1"
}
```

## Request

This section describes how to format the request to the service.

### URI fragment

The following parameters must be sent in the URI fragment.

Name	Type	Required	Description
userId	<a href="#">User-Id</a>	Yes	Id of the User which owns the Extension for which the event is added. It can take one of the following values: @me - refers to the <a href="#">authenticated User</a> . @viewer - also refers to the <a href="#">authenticated User</a> . @owner - refers to the User that owns the Extension used to make the phone call. User-Id - refers to the unique identifier of the User. Default: @me
extension	<a href="#">UAPI-Extension-Number</a>	Yes	The number of the Extension for which the event is added. Allowed Extension types: Phone Terminal, Queue, Conference, and IVR. Cannot be set to @self.

## Response

## Success

If successful, the request returns the Id of the newly created [PhoneCallEvent](#) and the following HTTP statuses:

HTTP Code	Description
200	The Id of the newly created PhoneCallEvent.
204	There is no Id to be returned.

## Failure

When it fails, the request returns the following error codes:

HTTP Code	Code	Description
400	p cet_type_inval id	Value supplied in type parameter is missing or invalid. The parameter must be set to one of the following value: 0 for DialIn, 1 for DialOut and 2 for Hangup.
400	p ce_method_i nvalid	Value supplied in method parameter is missing or invalid. The parameter must be set to one of the following value: 0 for GET or 1 for POST.
400	p ce_note_inva lid	Value supplied in note parameter is missing or invalid. It must be string and 1024 characters long.
400	p ce_url_inval id	Value supplied in request URL parameter is missing or invalid. It must be a valid HTTP URL.
400	p ce_status_in valid	Value supplied in status parameter is missing or invalid. The parameter must be set to one of the following value: 0 for enabled or 1 for disabled.
400	extension_inval id	Value supplied in the URI-Fragment as extension is invalid. The parameter must reference the number of an existing extension or cannot be set to @self.
400	p ce_access_d enied	You are not allowed to manage the phone call events.

## Examples

Below you can find an example that will help you understand the request and the response.

This example creates a phone call event for the Extension 0003\*210. The event is executed when a call is received and it makes a HTTP request to the script <http://myevent.com/SaveMyPhoneCallDetails> using the POST method.

The request is made by an App on behalf of a User.

HTTP Request
<pre>POST /uapi/extensions/@me/0003*210/phoneCallEvents HTTP/1.1 HOST uapi.voipnow.com Content Type: application/json Authorization: Bearer token  {   "type": "0",   "method": "0",   "note": "My phone call event is awesome",   "url": "http://myevent.com/SaveMyPhoneCallDetails",   "status": "1" }</pre>

Assuming that the request has been successful, the Service sends the following answer:

## HTTP Response

HTTP/1.1 201 Created

...

```
{
  "type": "0",
  "id": "NqeyDRqo4FtabmFj8gNWq3hsiGNYyq",
  "method": "0",
  "note": "My phone call event is awesome",
  "url": "http://myevent.com/SaveMyPhoneCallDetails",
  "status": "1",
  "modified": "2012-07-10T18:16:12+03:00",
  "links": { "self": "https://x.x.x.x/uapi/extensions/@me/0003*210/phoneCallEvents/MyPhoneCallEvent" }
}
```