

# Data Types

This page describes the data types that are specific to the UnifiedAPI.

- [UAPI-Caller-Id](#)
- [UAPI-Extension-Number](#)
- [UAPI-Phone-Number](#)
- [UAPI-Agent-ID](#)
- [Date](#)

## UAPI-Caller-Id

This data type is used when sending the caller name and phone number to the Service.

```
UAPI-Caller-Id = *( ALPHA / DIGIT / "<" / ">" / "+" / "*" )
```

## UAPI-Extension-Number

This data type is used to identify the format of the extension numbers.

```
UAPI-Extension-Number = *( DIGIT / "*" ) / "@self"
```

The reserved values are defined below:

Value	Description
@self	The extension number is always assigned to a User, so @self matches all the extensions under that User.

## UAPI-Phone-Number

This data type is used when sending a public phone number to the Service.

```
UAPI-Phone-Number = *( DIGIT / "+" )
```

## UAPI-Agent-ID

This data type is used to identify the queue agents.

```
UAPI-Agent-ID = *( DIGIT / "*" ) / *( DIGIT / "+" )
```

## Date

This data type must use the XML Schema dateTime format.

```
2015-01-23T04:56:22Z
```

Related Topics

[HTTP Return Codes](#)

[Quick Examples](#)

[API Client](#)