

# PhoneCallEvents Resource

This page describes the representation of the resources used by the Extension PhoneCallEvent Service.

## PhoneCallEvent resource

A phone call event is represented by the UnifiedAPI as a PhoneCallEvent resource.

### JSON representation

The example below contains the PhoneCallEvent in JSON representation. All fields are fictitious.

```
{
  "type": "0",
  "id": "NqeyDRqo4FtabmFj8gNWq3hsiGNYyq",
  "method": "0",
  "note": "My extension event is awesome",
  "url": "http://mynEvent.com/SaveMyPhoneCallDetails",
  "status": "1",
  "modified": "2012-07-10T18:16:12+03:00",
  "links": { "self": "https://x.x.x.x/uapi/extensions/@me/0003*210/phoneCallEvents/0/NqeyDRqo4FtabmFj8gNWq3hsiGNYyq" }
}
```

### PhoneCallEvent fields

Name	Type	Description
<b>type</b>	Number	Type of the Phone Call Event. <b>0</b> for Dial-In <b>1</b> for Dial-Out <b>2</b> for Hangup <b>3</b> for Answer incoming call <b>4</b> for Answer outgoing call
<b>id</b>	String	Id of the Phone Call Event. Must be alpha-numeric and 1 to 255 characters long.
<b>url</b>	String	The URL that is accessed when the extension receives, makes or terminates a phone call. Must be encoded using the <a href="#">RFC 3986</a> .
<b>method</b>	Number	The HTTP method used by the server to access the URL when an event occurs. <b>0</b> for GET <b>1</b> for POST
<b>status</b>	Number	The status of the event. <b>0</b> for disabled <b>1</b> for enabled
<b>note</b>	String	Notes about the event.
<b>modified</b>	<a href="#">Date</a>	Date when the event was last modified.

Related Topics

[Create PhoneCallEvents](#)

[Update PhoneCallEvents](#)

[List PhoneCallEvents](#)

[Delete PhoneCallEvents](#)