

PhoneCallEvents Resource

This page describes the representation of the resources used by the Extension PhoneCallEvent Service.

PhoneCallEvent resource

A phone call event is represented by the UnifiedAPI as a PhoneCallEvent resource.

JSON representation

The example below contains the PhoneCallEvent in JSON representation. All fields are fictitious.

```
{
  "type": "0",
  "id": "NqeyDRqo4FtabmFj8gNwq3hsiGNYyq",
  "method": "0",
  "note": "My extension event is awesome",
  "url": "http://mynEvent.com/SaveMyPhoneCallDetails",
  "status": "1",
  "modified": "2012-07-10T18:16:12+03:00",
  "links": { "self": "https://x.x.x.x/uapi/extensions/@me/0003*210/phoneCallEvents/0/NqeyDRqo4FtabmFj8gNwq3hsiGNYyq" }
}
```

PhoneCallEvent fields

Name	Type	Description
type	Number	Type of the Phone Call Event. 0 for Dial-In 1 for Dial-Out 2 for Hangup 3 for Answer incoming call 4 for Answer outgoing call
id	String	Id of the Phone Call Event. Must be alpha-numeric and 1 to 255 characters long.
url	String	The URL that is accessed when the extension receives, makes or terminates a phone call. Must be encoded using the RFC 3986 .
method	Number	The HTTP method used by the server to access the URL when an event occurs. 0 for GET 1 for POST
status	Number	The status of the event. 0 for disabled 1 for enabled
note	String	Notes about the event.
modified	Date	Date when the event was last modified.

- Related Topics
- [Create PhoneCallEvents](#)
 - [Update PhoneCallEvents](#)
 - [List PhoneCallEvents](#)
 - [Delete PhoneCallEvents](#)