

Update PhoneCallEvents

This method allows updating existing phone call events in particular contexts such as User, Organization or global.

- [Request/Response model](#)
 - [Overview](#)
 - [Request](#)
 - [Response](#)
- [Examples](#)

Request/Response model

Overview

Use this request to update a phone call event assigned to an Extension.

If successful, the Service returns the Id of the newly created [PhoneCallEvent](#), which is later used to [query the status](#) of the phone call event.

The request is made by an App that is registered to an User account.

To update existing phone call events, issue a HTTP PUT request:

Model

HTTP-Method

= "PUT"

[URI-Fragment](#)

= "/uapi/extensions/" User-Id "/" Extension-Number "/phoneCallEvents/" Event-Type "/"

Event-Id

Query-Parameters

= null

Request-Payload

= PhoneCallEvent

Return-Object

= PhoneCallEvent

Example

PUT /uapi/extensions/@me/0003*210/phoneCallEvents/0/MyPhoneCallEvent HTTP/1.1

HOST uapi.voipnow.com

Content Type: application/json

Authorization: Bearer token

{

"method": "1",

"note": "I want to use POST for my event"

}

Request

This section describes how to format the request to the service.

URI fragment

The following parameters must be sent in the URI fragment:

Name	Type	Required	Description
userId	User-Id	Yes	Id of the User which owns the Extension for which the event is added. It can take one of the following values: @me - refers to the authenticated User . @viewer - also refers to the authenticated User . @owner - refers to the User that owns the Extension used to make the phone call. User-Id - refers to the unique identifier of the User. Default: @me
extension	UAPI-Extension-Number	Yes	Number of the Extension for which the event is added. Allowed Extension types: Phone Terminal, Queue, Conference, and IVR. Cannot be set to @self.
eventType	Number	Yes	The type of the PhoneCallEvent.
eventId	Object-Id	Yes	The Id of an existing PhoneCallEvent.

Response

Success

If successful, the Service returns the Id of the newly created [PhoneCallEvent](#) and the following HTTP statuses:

HTTP Code	Description
200	The Id of the newly created phone call event is returned.
204	There is no Id to be returned.

Failure

When it fails, the request returns the following error codes:

HTTP Code	Code	Description
400	pce_type_invalid	Value supplied in type parameter is missing or invalid. The parameter must be set to one of the following value: 0 for DialIn, 1 for DialOut and 2 for Hangup.
400	pce_id_invalid	Value supplied in id parameter is invalid. The parameter must be set to an alpha-numeric 32 characters long.
400	pce_method_invalid	Value supplied in method parameter is missing or invalid. The parameter must be set to one of the following value: 0 for GET or 1 for POST.
400	pce_note_invalid	Value supplied in note parameter is missing or invalid. It must be string and 1024 characters long.
400	pce_url_invalid	Value supplied in request URL parameter is missing or invalid. It must be a valid HTTP URL.
400	pce_status_invalid	Value supplied in status parameter is missing or invalid. The parameter must be set to one of the following value: 0 for enabled or 1 for disabled.
400	extension_invalid	Value supplied in the URI-Fragment as extension is invalid. The parameter must reference the number of an existing extension or cannot be set to @self.
400	pce_access_denied	You are not allowed to manage the phone call events.

Examples

Below you can find an example that will help you understand the request and the response:

The example below updates the HTTP method of a event associated with the Extension 0003*210. The request is made by an App on behalf of a User.

HTTP Request
<pre>PUT /uapi/extensions/@me/0003*210/phoneCallEvents/0/NqeyDRqo4FtabmFj8gNWq3hsiGNYYqHTTP/1.1 HOST uapi.voipnow.com Content Type: application/json Authorization: Bearer token { "method": "1", "note": "I want to use POST for my event" }</pre>

Assuming that the request has been successful, the Service sends the following answer:

HTTP Response

HTTP/1.1 200 OK

...

```
{
  "type": "0",
  "id": "NqeyDRqo4FtabmFj8gNWq3hsiGNYyq",
  "method": "1",
  "note": "I want to use POST for my event",
  "url": "http://myevent.com/SaveMyPhoneCallDetails",
  "status": "1",
  "modified": "2012-07-10T18:16:12+03:00",
  "links": {"self": "https://x.x.x.x/uapi/extensions/@me/0003*210/phoneCallEvents/MyPhoneCallEvent"}
}
```